

IN THE CLAIMS

1

1. (Currently Amended) A pre-fill vaginal applicator, comprising:

a tubular barrel having a dispensing end provided with at least one opening formed therein and an open end;

5

said barrel having an inner surface;

a selectively removable closure closing said dispensing end of said barrel;

a resilient piston having first and second ends, selectively slidably positioned in said barrel;

10

said piston having an outer surface which is in sealing contact with said inner surface of said barrel to define a medication reservoir between said first end of said piston and said dispensing end of said barrel;

said second end of said piston having an opening extending thereinto which terminates between said first and second ends of said piston;

15

an elongated plunger having first and second ends adapted to be inserted into said open end of said barrel whereby said first end thereof may be inserted into said opening in said second end of said piston to detachably connect said plunger to said piston;

20

said piston, prior to insertion into said barrel, having a larger outside diameter than the inside diameter of said barrel whereby said piston is in a compressed state against said inner surface of said barrel when said piston is inserted into said barrel;

25

1

said plunger, when connected to said piston and being moved towards said dispensing
end of said barrel, causing said resilient piston to longitudinally stretch to permit
said piston to slide towards said dispensing end thereby forcing medication in
said medication reservoir to be ejected from said opening in said dispensing
end of said barrel;

5

said first end of said plunger being detachably connected to said piston whereby
movement of said plunger away from said piston will cause said first end of said
plunger to disconnect from said piston so that said piston remains in said barrel
thereby ensuring that the applicator may not be reused.

10

2. (Original) The applicator of claim 1 wherein said first end of said piston has
a portion thereof shaped so as to be receivable within said opening formed in said
dispensing end of said barrel.

15

3. (Currently Amended) The applicator of claim 1 wherein said piston is
constructed so as to destruct if an attempt is made to manually move said piston
towards said open end of said barrel by applying force against said first end thereof,
thereby further ensuring that the applicator may not be reused.

20

4. (Cancelled)

5. (Cancelled)

6. (Cancelled)

7. (Cancelled)

25

1 8. (Currently Amended) A vaginal applicator, comprising:
a tubular barrel having a dispensing end provided with at least one opening formed
therein and an open end;
said barrel having an inner surface;
5 a resilient piston having first and second ends, selectively slidably positioned in said
barrel;
said piston having an outer surface which is in slidable sealing contact with said inner
surface of said barrel to define a medication reservoir between said first end of
said piston and said dispensing end of said barrel;
10 said second end of said piston having an opening extending thereinto which
terminates between said first and second ends of said piston;
an elongated plunger having first and second ends adapted to be inserted into said
open end of said barrel whereby said first end of said plunger may be inserted
15 into said opening in said second end of said piston to detachably connect said
plunger to said piston;
said piston, prior to insertion into said barrel, having a larger outside diameter than the
inside diameter of said barrel whereby said piston is in a compressed state
20 against said inner surface of said barrel when said piston is inserted into said
barrel;
said plunger, when connected to said piston and being moved towards said dispensing
end of said barrel, causing said resilient piston to longitudinally stretch to permit
said piston to slide towards said dispensing end thereby forcing medication in
25

1

said medication reservoir to be ejected from said opening in said dispensing
end of said barrel;

5

said first end of said plunger being detachably connected to said piston whereby
movement of said plunger away from said piston will cause said first end of said
plunger to disconnect from said piston so that said piston remains in said barrel
thereby ensuring that the applicator may not be reused.

10

9. (Cancelled)

10. (Original) The applicator of claim 8 wherein said first end of said piston has
a portion thereof shaped so as to be receivable within said opening formed in said
dispensing end of said barrel.

15

11. (Original) The applicator of claim 8 wherein said piston is constructed so
as to destruct if an attempt is made to manually move said piston towards said open
end of said barrel by applying force against said first end thereof, thereby ensuring that
the applicator may not be reused.

20

12. (Cancelled)

13. (Cancelled)

14. (Cancelled)

15. (Cancelled)

16. (Cancelled)

25